



**Intertek**

UL & Warnock  
Hersey Listed

# EzyJamb Fire Rating Specifications

Single Swing Frames				
Positive Pressure tested to UL 10C				
Frame Type	Width	Height	Rating	Min. Wall Size
EZC - Classic Adjust	3' 4"	8' 0"	90	4-1/2"
SRC - Single Rabbet	4' 0"	10' 0"	90	4-1/2"
DRC - Double Rabbet	4' 0"	10' 0"	90	4-1/2"
ISD - Inswing	PENDING TESTING			

Pair Frames				
Positive Pressure tested to UL 10C				
Frame Type	Width	Height	Rating	Min. Wall Size
EZC - Classic Adjust	6' 0"	8' 0"	90	4-1/2"
SRC - Single Rabbet	6' 0"	10' 0"	90	4-1/2"
DRC - Double Rabbet	6' 0"	10' 0"	90	4-1/2"
ISD - Inswing	PENDING TESTING			

Hardware Approved for use					
Hardware Type	EZC	SRC	DRC	ISD	Rating
4-1/2" Hinges Emboss Prep.		✓	✓		90
4-1/2" Hinges Full Mortise		✓	✓		90
Surface Hinges - SS	✓	✓	✓		90
Concealed Hinges	✓	✓	✓		90
T-Strike Emboss Prep.	✓	✓	✓		90
T Strike Full Mortise		✓	✓		90
ASA Strike Emboss Prep.	✓	✓	✓		90
ASA Strike - Full Mortise		✓	✓		90
4-7/8" Full cutout electric strike		✓	✓		90
Concealed Closer cutout smaller than 3-23/32" Wide X 21-7/8" Long		✓	✓		90

All frames for compliance with the applicable requirements of the following criteria: NFPA 252 (2012) and UL 10C (2015) "Positive Pressure Fire Tests of Door Assemblies".

All frames can be used with steel stud, wood stud or masonry construction as long as the wall assembly is rated for 90 minutes. Fire Ratings do not apply to 1-3/8" Frames.

- Edge seals not required.
- All frames tested to positive pressure.
- Concealed Hinge 90 minute rating is max height 8-0' for SOSS and 9-0' for Tectus.

Information contained within this document supersedes all previous versions and is subject to change without notice

A Studco Innovation